

LUPES® TWIST



BENEFITS / FEATURES

DOES NOT HARDEN
SOFT HAND
DURABLE
HIGH BREAKING LOAD
EASY TO SPLICE

APPLICATIONS

LEECH LINE

SPECIFICATIONS

MATERIAL	100% HT POLYESTER FIBER
SPECIFIC GRAVITY	1,38 KG/DM ³
CONSTRUCTION	3 STRAND PLAITED
UV RESISTANCE	EXCELLENT
CHEMICAL RESISTANCE	GOOD
MELTING POINT	256°C
CRITICAL TEMPERATURE	170°C
ELONGATION AT BREAK	APPROX. %15-20
FIBER WATER ABSORPTION	APPROX. %1-2
WET ABRASION	GOOD
STANDARD	EN ISO 1141
LENGTH	100-200 M PLASTIC SPOOL

OTHER COLOURS & LARGER DIAMETERS UPON REQUEST

ART.NO	DIA	WEIGHT	B.LOAD
	(Ø)	(kg/100 m)	(kgf)*
014	4	1,21	280
014	5	1,90	430
014	6	2,73	610
014	8	4,85	1.080
014	10	7,57	1.630

*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

