

## LUPES® STANDARD



# KAYA ROPES

## UPGRADE YOUR LINES!

007 LUPES® STANDARD



## BENEFITS / FEATURES

SOFT HAND  
DOES NOT HARDEN  
DURABLE

## APPLICATIONS

DOCK LINE  
ANCHOR LINE  
TOWING LINE

## SPECIFICATIONS

MATERIAL	100% HT POLYESTER FIBER
TYPE	-
SPECIFIC GRAVITY	1,38 KG/DM <sup>3</sup>
CONSTRUCTION	COVER : 24-32 PLAITED, CORE : 12-16 PLAITED
UV RESISTANCE	EXCELLENT
CHEMICAL RESISTANCE	GOOD
MELTING POINT	256°C
CRITICAL TEMPERATURE	170°C
ELONGATION AT BREAK	APPROX.%15
FIBER WATER ABSORPTION	APPROX. %1-2
WET ABRASION	GOOD
DRY ABRASION	GOOD
COLOUR	BLACK - WHITE - NAVY BLUE - GREY - BLUE
STANDARD	ISO 10547
LENGTH	100-200 M ORANGE SPOOL OR COIL

OTHER COLOURS ON REQUEST

ART.NO	DIA	WEIGHT	B.LOAD
	(Ø)	(kg / 100 m)	(kgf)*
007	8	5,10	1.550
007	10	7,97	2.330
007	12	11,50	3.270
007	14	15,60	4.370
007	16	20,40	5.630
007	18	25,80	7.000
007	20	31,90	8.600
007	22	38,60	10.300
007	24	45,90	13.100
007	26	53,90	15.100
007	28	62,50	17.300
007	30	71,70	19.600
007	32	81,60	22.000
007	36	100,30	27.400
007	40	128,00	33.000
007	48	184,00	46.000
007	56	250,00	62.000
007	64	326,00	80.000
007	72	413,00	100.000
007	80	510,00	123.000
007	88	617,00	148.000
007	96	735,00	175.000

\*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

