



018 LUPP® SQUARE


BENEFITS / FEATURES

DOES NOT HARDEN
DOES NOT KINK
SOFT HAND
ECONOMICALLY PRICED
BUOYANT
EASY TO SPLICE

APPLICATIONS

DOCK LINE
TOWING LINE

SPECIFICATIONS

MATERIAL	100% HT POLYPROPYLENE FIBER
TYPE	L
SPECIFIC GRAVITY	0,91 KG/DM ³
CONSTRUCTION	8 STRAND PLAITED (4X2)
UV RESISTANCE	SUFFICIENT
CHEMICAL RESISTANCE	VERY GOOD
MELTING POINT	165°C
CRITICAL TEMPERATURE	80°C
ELONGATION AT BREAK	APPROX.%23
FIBER WATER ABSORPTION	NONE
WET ABRASION	SUFFICIENT
DRY ABRASION	SUFFICIENT
COLOUR	BLACK-WHITE-NAVY BLUE-ORANGE
STANDARD	EN ISO 1346
LENGTH	100-200 M PLASTIC/WOODEN SPOOL OR COIL

OTHER COLOURS ON REQUEST

ART.NO	DIA (Ø)	WEIGHT (kg/100 m)	B.LOAD (kgf)*
018	12	6,51	2.280
018	14	8,86	3.225
018	16	11,60	4.310
018	18	14,60	5.350
018	20	18,10	6.500
018	22	21,90	7.740
018	24	26,00	9.060
018	26	30,60	10.500
018	28	35,40	12.900
018	30	40,70	14.600
018	32	46,30	16.400
018	36	58,60	20.100
018	40	72,30	24.300

*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

