



110 LUPES® EUROPA



BENEFITS / FEATURES

- DOES NOT HARDEN
- DOES NOT KINK
- SUPERIOR SOFT HAND
- DURABLE
- FLEXIBLE COVER
- HIGH BREAKING LOAD

APPLICATIONS

- DOCK LINE
- ANCHOR LINE
- TOWING LINE

SPECIFICATIONS

MATERIAL	100% HT POLYESTER FIBER
TYPE	-
SPECIFIC GRAVITY	1,38 KG/DM ³
CONSTRUCTION	COVER: 24 PLAITED, CORE: 12 PLAITED
UV RESISTANCE	EXCELLENT
CHEMICAL RESISTANCE	GOOD
MELTING POINT	256°C
CRITICAL TEMPERATURE	170°C
ELONGATION AT BREAK	APPROX.%15
FIBER WATER ABSORPTION	APPROX. %1-2
WET ABRASION	GOOD
DRY ABRASION	GOOD
COLOUR	NAVY BLUE-BLACK
STANDARD	-
LENGTH	100-200 M WOODEN SPOOL OR COIL

OTHER COLOURS ON REQUEST

ART.NO	DIA	WEIGHT	B.LOAD
	(Ø)	(kg/100 m)	(kgf)*
110	24	42,80	11.500
110	28	57,15	15.000
110	32	76,45	20.000
110	36	95,75	24.000
110	40	117,50	28.500

*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

