

## LUPP® CORD



309 LUPP® CORD



## APPLICATIONS

OTHER FISHING LINES

SEE PAGES 8-9

## SPECIFICATIONS

MATERIAL	COVER : HT POLYPROPYLENE FIBER CORE : HT POLYPROPYLENE FIBER
SPECIFIC GRAVITY	0,91 KG/DM <sup>3</sup>
CONSTRUCTION	COVER : 16-20-24 PLAITED, CORE : 12-16 PLAITED
UV RESISTANCE	SUFFICIENT
CHEMICAL RESISTANCE	VERY GOOD
MELTING POINT	165°C
CRITICAL TEMPERATURE	80°C
WORKING STRETCH	<8%
FIBER WATER ABSORPTION	NONE
WET ABRASION	SUFFICIENT
LENGTH	100-200 M ORANGE SPOOL OR COIL

OTHER COLOURS UPON REQUEST

## BENEFITS / FEATURES

MODERATE ELONGATION  
DOES NOT HARDEN  
BUOYANT  
ECONOMICALLY PRICED

ART.NO	DIA (mm)	WEIGHT (kg / 100 m)	B.LOAD * (kgf)
	(Ø)		
309	2	0,18	70
309	2,5	0,28	105
309	3	0,40	150
309	4	0,73	280
309	5	1,13	430
309	6	1,63	600

\*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

