

TANKER SQUARE



KAYA ROPES

UPGRADE YOUR LINES!

036 - TANKER SQUARE



BENEFITS / FEATURES

- GOOD BREAKING LOAD
- GOOD SHOCK ABSORPTION
- DOES NOT KINK
- FLEXIBLE
- DURABLE
- GENERAL ACCORDANCE WITH OCIMF GUIDELINE

APPLICATIONS

- VESSEL PRIMARY MOORING LINE
- VESSEL SECONDARY MOORING LINE
- VESSEL GENERAL WORKING LINE
- VESSEL TOW LINE
- TUG BARGE TIE-UP LINE
- TUG BARGE AND DREDGE WORKING LINE
- TUG H-BITT WORKING LINE
- TRAWL/BRIDLE LINE

SPECIFICATIONS

MATERIAL	100% HT POLYOLEFIN & POLYESTER MIX FIBER
TYPE	L
SPECIFIC GRAVITY	1,10 KG/DM ³
CONSTRUCTION	8 STRAND PLAITED (4X2)
UV RESISTANCE	GOOD
CHEMICAL RESISTANCE	VERY GOOD
MELTING POINT	165°C
CRITICAL TEMPERATURE	80°C
ELONGATION AT BREAK	APPROX.19%
FIBER WATER ABSORPTION	0,15%
WET ABRASION	GOOD
DRY ABRASION	GOOD
COLOUR	WHITE - ORANGE
STANDARD	ISO 10556
LENGTH	200-220 M COIL

OTHER COLOURS & LARGER DIAMETERS UPON REQUEST

ART.NO	DIA (mm)	WEIGHT (kg / 100 m)	B.LOAD * (kgf)
	(Ø)		
036	40	88,40	30.000
036	48	128,00	46.290
036	56	172,00	67.800
036	64	225,00	82.600
036	72	285,00	102.000
036	80	352,00	125.500
036	88	502,00	156.000
036	96	598,00	185.000

*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

