

LUPA® TARGET



KAYA ROPES

UPGRADE YOUR LINES!

508 LUPA® TARGET



APPLICATIONS

TARGET ROPE

SPECIFICATIONS

MATERIAL	100% HT POLYAMIDE FIBER
TYPE	-
SPECIFIC GRAVITY	1,14 KG/DM ³
CONSTRUCTION	COVER : 32 PLAITED / CORE : 3x16 PLAITED
UV RESISTANCE	VERY GOOD
CHEMICAL RESISTANCE	GOOD
MELTING POINT	218°C
CRITICAL TEMPERATURE	130°C
ELONGATION AT BREAK	APPROX.%30-35
FIBER WATER ABSORPTION	APPROX. %3-4
WET ABRASION	SUFFICIENT
DRY ABRASION	GOOD
COLOUR	WHITE
STANDARD	-
LENGTH	500 M ORANGE SPOOL OR COIL

OTHER COLOURS ON REQUEST



ART.NO	DIA (Ø)	WEIGHT (kg / 100 m)	B.LOAD (kgf)*
508	11,7 (± 0,6)	7,65 (± 6,5)	2.340

*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)



BENEFITS / FEATURES

- HIGH STRENGTH
- EXCELLENT SHOCK ABSORPTION
- HIGH STRETCH
- DURABLE
- SOFT HAND
- DOES NOT KINK

