

ROCK D® MIX



202 ROCK D® MIX



BENEFITS / FEATURES

GOOD PERFORMANCE IN JAMMERS
LOW STRETCH
EASY TO SPLICE

APPLICATIONS

REEFING LINES

SPECIFICATIONS

MATERIAL	COVER: HT POLYESTER FIBER CORE: COATED DYNEEMA® SK 78
SPECIFIC GRAVITY	0,99-1,20 KG/DM³
CONSTRUCTION	COVER: 20-24 PLAITED, CORE: 16 PLAITED
UV RESISTANCE	EXCELLENT
CHEMICAL RESISTANCE	GOOD
MELTING POINT	147°C-256°C
CRITICAL TEMPERATURE	65°C
WORKING STRETCH	<1,5%
FIBER WATER ABSORPTION	APPROX. %0-1
WET ABRASION	GOOD
LENGTH	100-200 M PLASTIC SPOOL

OTHER COLOURS & LARGER DIAMETERS UPON REQUEST

ART.NO	DIA (Ø)	WEIGHT (kg/100 m)	B.LOAD (kgf)*
202	3	0,95	420
202	4	1,10	820
202	5	1,55	1.300
202	6	2,45	1.850
202	7	3,30	2.750

*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

KAYA
ROPESUPGRADE
YOUR
LINES!