

## DYNE K® SBF



# KAYA ROPES

## UPGRADE YOUR LINES!



405-605 DYNE K® SBF 78/79



## BENEFITS / FEATURES

SUPERIOR BENDING FATIGUE (SBF)  
EXCELLENT BREAKING LOAD (SK99)  
BUOYANT  
DURABLE  
VERY LOW STRETCH  
LIGHTWEIGHT  
EASY TO SPLICE  
DOES NOT KINK

## APPLICATIONS

MAIN HALYARD

## SPECIFICATIONS

MATERIAL	COATED DYNEEMA® SK 78/99
SPECIFIC GRAVITY	0,97 KG/DM³
CONSTRUCTION	12 STRAND BRAIDED
UV RESISTANCE	EXCELLENT
CHEMICAL RESISTANCE	EXCELLENT
MELTING POINT	147°C
CRITICAL TEMPERATURE	65°C
WORKING STRETCH	<1%
FIBER WATER ABSORPTION	NONE
WET ABRASION	EXCELLENT
DRY ABRASION	EXCELLENT
LENGTH	100-200 M PLASTIC SPOOL

OTHER COLOURS &amp; LARGER DIAMETERS UPON REQUEST

ART.NO	DIA (Ø)	WEIGHT (kg/100 m)	B.LOAD (kgf)*	
			SK78 (ART.NO: 005)	SK99 (ART.NO: 505)
405-605	2	0,25	425	502
405-605	3	0,50	950	1.121
405-605	4	0,95	1.650	1.947
405-605	5	1,50	2.600	3.068
405-605	6	2,30	3.750	4.425
405-605	8	4,00	6.600	7.788

\*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

