


## OVERPOWER



## BENEFITS / FEATURES

EXCELLENT DURABILITY  
LOW STRETCH  
HIGH STRENGTH

## APPLICATIONS

WINDSURF OUTHAULS/DOWNSHAULS

## SPECIFICATIONS

MATERIAL	COATED DYNEEMA® SK 78
SPECIFIC GRAVITY	0,97 KG/DM <sup>3</sup>
CONSTRUCTION	12 STRAND BRAIDED
UV RESISTANCE	EXCELLENT
CHEMICAL RESISTANCE	EXCELLENT
MELTING POINT	147°C
CRITICAL TEMPERATURE	65°C
WORKING STRETCH	<2%
FIBER WATER ABSORPTION	NONE
WET ABRASION	EXCELLENT
DRY ABRASION	EXCELLENT
LENGTH	100-200 M PLASTIC SPOOL

OTHER COLOURS & LARGER DIAMETERS UPON REQUEST

ART.NO	DIA	WEIGHT	B.LOAD
	(Ø)	(kg/100 m)	(kgf)*
905	3,8	0,90	650

\*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

# KAYA ROPES

## UPGRADE YOUR LINES!

