

DYNE K®




KAYA ROPES

UPGRADE YOUR LINES!



005-505 DYNE K® 78/99



BENEFITS / FEATURES

- SUPERIOR ABRASION RESISTANCE
- EXCELLENT BREAKING LOAD (SK99)
- BUOYANT
- DURABLE
- VERY LOW STRETCH
- LIGHTWEIGHT
- EASY TO SPLICE
- DOES NOT KINK

APPLICATIONS

PARASAILING LINE

SPECIFICATIONS

MATERIAL	COATED DYNEEMA® SK 78/99
SPECIFIC GRAVITY	0,97 KG/DM ³
CONSTRUCTION	12 STRAND BRAIDED
UV RESISTANCE	EXCELLENT
CHEMICAL RESISTANCE	EXCELLENT
MELTING POINT	147°C
CRITICAL TEMPERATURE	65°C
WORKING STRETCH	<1%
FIBER WATER ABSORPTION	NONE
WET ABRASION	EXCELLENT
DRY ABRASION	EXCELLENT
LENGTH	100-200 M PLASTIC SPOOL

OTHER COLOURS & LARGER DIAMETERS UPON REQUEST

ART.NO	DIA (Ø)	WEIGHT (kg/100 m)	B.LOAD (kgf)*	
			SK78 (ART.NO: 005)	SK99 (ART.NO: 505)
005-505	6	2,30	3.750	4.425
005-505	8	4,00	6.600	7.788
005-505	10	6,10	10.400	12.272
005-505	12	8,70	16.600	17.700

*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

