

LUPES® VIPERA



KAYA ROPES

UPGRADE YOUR LINES!



010 LUPES® VIPERA

APPLICATIONS

DOCK LINE
ANCHOR LINE
TOWING LINE

SPECIFICATIONS

MATERIAL	100% HT POLYESTER FIBER
TYPE	-
SPECIFIC GRAVITY	1,38 KG/DM ³
CONSTRUCTION	COVER: 16-20-24 PLAITED, CORE: 16 PLAITED
UV RESISTANCE	EXCELLENT
CHEMICAL RESISTANCE	GOOD
MELTING POINT	256°C
CRITICAL TEMPERATURE	170°C
ELONGATION AT BREAK	APPROX.%15
FIBER WATER ABSORPTION	APPROX. %1-2
WET ABRASION	GOOD
DRY ABRASION	GOOD
COLOUR	WHITE-NAVY BLUE-BLACK
STANDARD	-
LENGTH	100-200 M PLASTIC/WOODEN SPOOL OR COIL

OTHER COLOURS ON REQUEST



ART.NO	DIA (Ø)	WEIGHT (kg/100 m)	B.LOAD (kgf)*
010	8	4,85	1.320
010	10	7,45	2.050
010	12	11,00	2.900
010	14	14,80	3.910
010	16	19,35	5.070
010	18	24,80	6.370
010	20	30,40	7.800
010	22	36,85	9.380
010	24	43,65	11.110
010	26	51,25	12.450
010	28	59,25	14.990

*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)



BENEFITS / FEATURES

DOES NOT HARDEN
DOES NOT KINK
SOFT HAND
DURABLE
FLEXIBLE COVER
HIGH BREAKING LOAD

