

LUPP® TWIST



KAYA ROPES

UPGRADE YOUR LINES!

015 LUPP® TWIST



APPLICATIONS

DOCK LINE
TOWING LINE

SPECIFICATIONS

MATERIAL	100% HT POLYPROPYLENE FIBER
TYPE	A
SPECIFIC GRAVITY	0,91 KG/DM ³
CONSTRUCTION	3 STRAND
UV RESISTANCE	SUFFICIENT
CHEMICAL RESISTANCE	VERY GOOD
MELTING POINT	165°C
CRITICAL TEMPERATURE	80°C
ELONGATION AT BREAK	APPROX.%23
FIBER WATER ABSORPTION	NONE
WET ABRASION	SUFFICIENT
DRY ABRASION	SUFFICIENT
COLOUR	WHITE-NAVY BLUE-BLACK-BLUE
STANDARD	EN ISO 1346
LENGTH	100-200 M PLASTIC/WOODEN SPOOL OR COIL

OTHER COLOURS ON REQUEST



BENEFITS / FEATURES

DOES NOT HARDEN
SOFT HAND
ECONOMICALLY PRICED
BUOYANT
EASY TO SPLICE

ART.NO	DIA	WEIGHT	B.LOAD
	(Ø)	(kg/100 m)	(kgf)*
015	4	0,72	320
015	5	1,13	480
015	6	1,63	680
015	8	2,89	1.200
015	10	4,52	1.730
015	12	6,51	2.550
015	14	8,86	3.410
015	16	11,60	4.330
015	18	14,60	5.400
015	20	18,10	6.500
015	22	21,90	7.740
015	24	26,00	9.180
015	26	30,60	10.810
015	28	35,40	12.900
015	30	40,70	14.600
015	32	46,30	16.400
015	36	58,60	20.100
015	40	72,30	24.300
015	48	104,00	34.170
015	56	142,00	44.600
015	64	185,00	57.120

*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

