

DYNE COVER



105 DYNE COVER



BENEFITS / FEATURES

- IDEAL FOR PROTECTION AGAINST ABRASION
- EXCELLENT PERFORMANCE IN JAMMERS
- EASY HANDLING
- BUOYANT

APPLICATIONS

SPECIAL COVER

SPECIFICATIONS

MATERIAL	100% DYNEEMA® SK 78 FIBER
SPECIFIC GRAVITY	0,97 KG/DM ³
CONSTRUCTION	24-32 PLAITED
UV RESISTANCE	EXCELLENT
CHEMICAL RESISTANCE	EXCELLENT
MELTING POINT	147°C
CRITICAL TEMPERATURE	65°C
WORKING STRETCH	<3%
WET ABRASION	EXCELLENT
DRY ABRASION	EXCELLENT
STANDARD	-
LENGTH	100-200 M PLASTIC SPOOL

LARGER DIAMETERS UPON REQUEST

ART.NO	DIA	WEIGHT	B.LOAD
	(Ø)	(kg/100 m)	(kgf)*
105	4-6	-	-
105	5-7	-	-
105	6-8	-	-
105	7-10	-	-
105	8-12	-	-
105	10-16	-	-
105	12-20	-	-

*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

KAYA ROPES

UPGRADE YOUR LINES!

