

LUPP® CORD



309 LUPP® CORD



BENEFITS / FEATURES

OUTSTANDING FLEXIBILITY
ECONOMICALLY PRICED
LOW STRETCH
BUOYANT

APPLICATIONS

CONTROL LINE

SEE PAGE 47

SPECIFICATIONS

MATERIAL	COVER: HT POLYPROPYLENE FIBER CORE: HT POLYPROPYLENE FIBER
SPECIFIC GRAVITY	0,91 KG/DM ³
CONSTRUCTION	COVER: 16-20 PLAITED, CORE: PARALLEL BRAIDED
UV RESISTANCE	SUFFICIENT
CHEMICAL RESISTANCE	VERY GOOD
MELTING POINT	165°C
CRITICAL TEMPERATURE	80°C
WORKING STRETCH	<6%
FIBER WATER ABSORPTION	NONE
WET ABRASION	SUFFICIENT
LENGTH	100-200 M PLASTIC SPOOL

OTHER COLOURS & LARGER DIAMETERS UPON REQUEST

ART.NO	DIA (Ø)	WEIGHT (kg/100 m)	B.LOAD (kgf)*
309	4	0,75	250
309	5	1,15	400
309	6	1,60	550

*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

KAYA ROPES

UPGRADE YOUR LINES!

