

DINGHY ROCK D® MIX TP



KAYA ROPES

UPGRADE YOUR LINES!



713 DINGHY ROCK D® MIX TP



BENEFITS / FEATURES

GOOD GRIP ON WINCHES
 VERY GOOD PERFORMANCE IN JAMMERS
 VERY GOOD HEAT RESISTANCE
 LOW STRETCH
 EASY TO SPLICE

APPLICATIONS

MAIN SHEET

SPECIFICATIONS

MATERIAL	COVER: TECHNORA® & HT POLYESTER FIBER CORE: COATED DYNEEMA® SK 78
SPECIFIC GRAVITY	0,99-1,20 KG/DM ³
CONSTRUCTION	COVER: 20-24 PLAITED, CORE: 16 PLAITED
UV RESISTANCE	SUFFICIENT
CHEMICAL RESISTANCE	EXCELLENT
MELTING POINT	147°C-256°C
CRITICAL TEMPERATURE	65°C
WORKING STRETCH	<1,5%
FIBER WATER ABSORPTION	APPROX. %1-2
WET ABRASION	EXCELLENT
LENGTH	100-200 M PLASTIC SPOOL

OTHER COLOURS & LARGER DIAMETERS UPON REQUEST

ART.NO	DIA	WEIGHT	B.LOAD
	(Ø)	(kg/100 m)	(kgf)*
713	4	1,25	925
713	5	1,70	1.350
713	6	2,60	2.250

*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

