

LUPA® CORD



BENEFITS / FEATURES

HIGH STRENGTH
EXCELLENT SHOCK ABSORPTION
HIGH STRETCH
DURABLE
SOFT HAND

APPLICATIONS

LUFF LINE / LEECH LINE

SPECIFICATIONS

MATERIAL	COVER : HT POLYAMIDE FIBER CORE : HT POLYAMIDE FIBER
SPECIFIC GRAVITY	1,14 KG/DM ³
CONSTRUCTION	COVER : 16-20-24 PLAITED, CORE : 12-16 PLAITED
UV RESISTANCE	VERY GOOD
CHEMICAL RESISTANCE	GOOD
MELTING POINT	218°C
CRITICAL TEMPERATURE	130°C
WORKING STRETCH	<12%
FIBER WATER ABSORPTION	APPROX. %3-4
WET ABRASION	SUFFICIENT
LENGTH	100-200 M ORANGE SPOOL OR COIL

OTHER COLOURS & LARGER DIAMETERS UPON REQUEST

ART.NO	DIA (Ø)	WEIGHT (kg / 100 m)	B.LOAD (kgf)*
108	2	0,25	120
108	2,5	0,40	135
108	3	0,60	195
108	4	1,05	330
108	5	1,60	510
108	6	2,24	730

*UNSPliced BREAK LOAD (ALL TESTS ARE IN ACCORDANCE WITH ISO 2307)

KAYA
ROPES

UPGRADE
YOUR
LINES!

